



IBC AGITATOR



TECHNICAL SPECIFICATIONS

- Different stirring elements and agitator speeds possible, adapted to your application, product density, viscosity and solid content
- Lockable IBC fastening crossbeam for IBC containers 400 to 2,500 litre capacity
- Addition of liquids under stirring possible, by connection nozzle at the IBC mounting crossbar
- Material: stainless steel 304 / 316Ti (product contacted parts)
- Geared motors in various power ratings optional with speed adjustment via attached frequency converter
- On/Off switch with motor protection and CEE plug with low voltage release

FIELD OF APPLICATIONS

Example applications for the IBC agitator:

- Water treatment
- chemical industry
- Paints and Lacquers
- Textiles
- Wood Materials Industry
- Dilution
- Suspension
- Homogenisation
- Dispersion



CHEMISTRY



PAINT AND VARNISH



CONSTRUCTION MATERIAL



WOOD-BASED PANELS



ENVIRONMENTAL ENGINEERING



WE ARE LOOKING FORWARD TO YOUR INQUIRY

IFA Technology GmbH, Jurastraße 10, 86641 Rain am Lech, Germany
Tel. +49 9090 70570-0, vertrieb@ifa-technology.de, www.ifa-technology.de



Member of  Deuretech Group